

FH-408 FTTH Termination Box

FH-408 termination box is designed for use in residential and business applications. It can hold 1SC adaptor, 1RJ45 and 1RJ11. The unit can be quickly installed in office house or communication room.

Features

- ✓ Ability to allow cables to enter from both sides of the unit
- ✓ Removable cover for easy access Compact, low profile, wall mounted unit used for small and large business premises

Technical Data

Number of input cable ports: 4

Maximum Capacity: 2 fibers

Dimension: 86 mm x 86 mm x30.5mm



Specifications & Ordering Information

Order No	Dimensions LxWxH(mm)	Cable Ports	Spliced Fiber Storage Capacity	Adaptor Capacity
ALF-FH-408	86x86x30.5	4 Cable ports (for cables with max diameter 5 mm)	2 Splices	1 SC Simplex Adaptors, 1 RJ45 and 1 RJ11

FH-508 FTTH Termination Box

The FH-508 is a small size termination box to allow to break out fibers from a riser cable to individual drop cable that bring the fiber from this point to the living units of an MDU. The FH-508 is designed for riser cables that allow access through a small window cut or incision. For cable constructions that require larger window cuts, fiber overlength can be stored in the base module. To connect the drop fibers to the riser fibers both splices and connector can be used. The splice capacity of the FH-508 splice module is 4 splices.

Features

- ✓ Very compact enclosure with dimensions
- ✓ Window cuts as small as 50mm possible with specific cable constructions such as the Mini-breakout cable
- ✓ Free breathing enclosure for indoor use
- ✓ Front accessible
- ✓ Wrap around riser cable installation
- ✓ Not required to cut loop-through fibers from riser cable
- ✓ Can hold 4 LC connectors or 2 SC connectors
- ✓ Compatible with mechanical splice, heat shrink protectors in the same splice holder
- ✓ Drop cable diameter up to 5mm
- ✓ Main cable diameter up to 10,5mm

Kit Content

- ✓ Base module for main cable management
- ✓ Splice module
- ✓ Cover
- ✓ Main and drop cable fixation accessories

Specifications & Ordering Information

Order No	Dimensions LxWxH(mm)	Cable Ports	Spliced Fiber Storage Capacity	Adaptor Capacity
ALF-FH-508	108.5x85x27	Drop Cable diameter up to 5 mm Main Cable diameter up to 10 mm	4 Splices	2 SC Simplex or 2 LC Duplex Adaptors

